



Product Specification Report Key Attributes



SmartBugOff (H)

Product ID: SS-C3500H

High pH Vehicle Bug Remover

Description


An Ultra Concentrated liquid high foaming Hi pH pre-soak formulated to remove insect and other organic based contaminants from painted vehicle surfaces in one application.

Features

- Economical
- Versatile
- Free Rinsing
- Environmentally Desirable (Eco Friendly)
- Saves time and labor

Benefits

- At dilutions never before seen in the industry, washing 10X more vehicles per gallon than any of the competitors products.
- Can be applied with low-pressure, in hot or cold water. For best results, blend with treated water. Always rinse with high or medium pressure water.
- Contains no phosphates or solvents.
- Cleans effectively



Applications

An excellent, economical truck and trailer wash formulated for low, and high-pressure applications. Highly effective on exhaust deposits, road film, and bug residue. Recommend to use air injection to boost foaming ability. Allow 10-15 seconds of dwell time. Recommended to be applied after low pH pre-soak in touch-free applications. Must be removed with medium or high-pressure water.

Types of Operations

- Tunnel Washes
- In-Bay Automatics
- Self Serve Washes

Type of Equipment

- Touchless Drive-Thru and Gantry Machines
- Friction Drive-Thru and Gantry Machines
- Pressure Washer Systems

Water Types

- Revers Osmosis Water
- Natural Water (City or Well)
- Soft Water

Specifications

Physical Form Liquid
 Color Amber
 Odor Characteristic
 pH (Concentrate) . . .13 ~13.5
 (1% solution) 11 ~ 11.5

Density - Specific Gravity9.46 lbs. / gal. ~ 1.13
 D.O.T. ShippingUN 1824
 Flash Point (TCC) None
 Shelf Life1 year

Packaging

- Sizes:**
- 1 Gallon Bottle
 - 5 Gallon Pail
 - 30 Gallon Drum

Smart Solutions Sales and Support
www.smartsolutions.net